



CERTIFIED
PORCELAIN
TILE

WATERWOOD™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC WITH REVEAL IMAGING®

FLOOR



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

WATERWOOD™

Inspired by the bricola wood pillars that grace the waterways of Venice, this unique wood-look tile is not your everyday oak look. This wood is transformed by years of water exposure into a unique look found in only one place in the world. Graceful porcelain planks in 8x40 or a 1½ inch hexagon mosaic are perfect complements to uncommon designs.

Cover photo features Waterwood Classic Oak 8 x 40 on the floor and White Oak 8 x 40 on the wall.

Above photo features Waterwood Natural Oak 8 x 40 on the floor, White Oak 8 x 40 on the side wall, Natural Oak Hexagon mosaic on the bar and Bricktown™ Greige Parkway 4 x 8 on the bar walls.

WATERWOOD™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC
WITH REVEAL IMAGING®

GLAZED PORCELAIN FLOOR TILE



WHITE OAK WD15



WEATHERED OAK WD18



NATURAL OAK WD16



CLASSIC OAK WD17

GLAZED CERAMIC MOSAIC



WHITE OAK WD15



WEATHERED OAK WD18



NATURAL OAK WD16





CLASSIC OAK WD17

WATERWOOD™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC WITH REVEAL IMAGING®

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	8 x 40 Floor Tile	7-7/8" x 39-3/8" (20.00 cm x 100.00 cm)	5/16"	10.75	5
	1-1/2 x 1-1/2 Hexagon Mosaic ■ ■	11-3/8" x 10-1/4" Sheet (28.89 cm x 26.04 cm Sheet)	1/4"	9.72	12

- Dot-mounted
- Ceramic body

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

Mosaic: 1/8"

RELATIVE PRICING: Medium

SHADE VARIATION



HIGH
(V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbs.	> 250 lbs.
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	3	3

For additional information on test results, visit us at: americanolean.com/information/TestResults.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	●*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	●*

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Mosaic tile only

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.



POST-CONSUMER
RECYCLED MATERIALS



REVEAL IMAGING®



PRE-CONSUMER
RECYCLED MATERIALS



MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE

©2019 AMERICAN OLEAN (02/19)



AMERICAN OLEAN®
PROVEN IN TILE™